

Fittings / LED Bulkheads


Aqua1 9/14/18W LED CCT White Bulkhead with Microwave Sensor



This cost-effective, colour switchable bulkhead is IP65 as standard, with the benefits of a high transmission frosted diffuser and rear, side & BESA Box cable entry. It is an ideal replacement for 28W 2D fittings.

- CCT Cool White / Warm White / Daylight (3/4/6000K).
- High transmission frosted diffuser.
- IP65 sealed fitting.
- Rear, Side & BESA Box cable entry.
- Emergency, microwave and corridor dimming options.

Technical Specification



| | |
|---------------------|-------|
| Product Code | 11602 |
|---------------------|-------|

Reference

| | |
|------------------|---------|
| Guarantee | 7 Years |
|------------------|---------|

| | |
|------------|---------------|
| EAN | 5013588116020 |
|------------|---------------|

| | |
|-----------------------|------------|
| Commodity Code | 9405109890 |
|-----------------------|------------|

| | |
|--------------------------|----|
| Country of Origin | CN |
|--------------------------|----|

| | |
|--------------------|----------|
| UNSPSC Code | 39111612 |
|--------------------|----------|

Technical Specification

| | |
|--------------------------------|----------------|
| Volts (V) | 220/240 |
| Watts (W) | 9/14/18 |
| Colour Temp (K) | 3000/4000/6000 |
| Dimmable? | No |
| Lumens (lm) | 870-1700 |
| Candelas (cd) | 372-699 |
| Life Hours | 50000 |
| Beam Angle | 116° |
| Energy Rating | C |
| CRI (Ra) | 80 |
| Switching Cycles | 30000 |
| Frequency (Hz) | 50 |
| LED Drive Current | 130mA |
| Energy Consumption (kWh/1000h) | 9/14/18 |
| IP Rating | IP65 |
| Impact Protection | IK10 |

Dimensions

| | |
|---------------|-----|
| Depth (mm) | 110 |
| Diameter (mm) | 335 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 113 |
| Single Carton Width (mm) | 340 |
| Single Carton Depth (mm) | 343 |
| Single Carton Weight (kg) | 1.178 |
| Individual Volume | 0.01318 |
| Inner Box Qty | 1 |
| Outer Box Qty | 8 |
| Outer Box Height (mm) | 700 |
| Outer Box Width (mm) | 460 |
| Outer Box Depth (mm) | 360 |
| Outer Box Weight (kg) | 10.9 |