



Features :

- **Interchangeable AC Heads**
- **DOE Level VI Efficiency**
- **Overcurrent Protection**
- **Short Circuit Protection**
- **RoHs Compliant**
- **1 Year Warranty**
- **EN62368 Approved**

Model	ECM-5-5-USB	ECM-10-5USB
-------	-------------	-------------

Output	DC Voltage	5vdc	5vdc
	Rated Current	1amp	2amp
	Current Range	0-1amp	0-2amp
	Rated Power	5 Watt	10 Watt
	Ripple & Noise	300mVp-p max	300mVp-p max
	Output Regulation	±5%	±5%
	Output Connector	USB Socket	USB Socket
Input	Voltage Range	90-264vac	90-264vac
	Frequency Range	47-63Hz	47-63Hz
	Input Current	0.3amp Max	0.3amp Max
	Inrush Current	40amp Max	40amp Max
	Standby Power	0.075W Max	0.075W Max
	Leakage Current	0.25amp Max	0.25amp Max
	Input Connector	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads
Environment	Operating Temp	0°C~40°C	0°C~40°C
	Cooling	Convection	Convection
	Temperature Coefficient	0.05%/°C	0.05%/°C
	Humidity	5~95%RH(non-condensing)	5~95%RH(non-condensing)
	Storage Temp	-20°C~+60°C	-20°C~+60°C
Safety & EMC	Safety Standards	UL/CUL 62368-1, GS/TUV EN62368-1, SAA AS/NZ 60950.1, CCC GB4943.1	
	EMC Emissions	EN55032,RCM GB9254, FCC Part 15 Class B	
General	Dimensions	47.3 x 37.8 x 26.7mm	61.9 x 39 x 32.4mm
	Weight	26g	53g
	Carton Quantity	120	120