



CorePro GLASS LED candles and lusters



CorePro LEDLusterND2-25W P45 E27 827 CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	250 lm
Luminous Efficacy (rated) (Nom)	125.00 lm/W
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	

Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	2 W
Lamp Current (Nom)	20 mA
Wattage Equivalent	25 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	30 ℃


Datasheet, 2024, July 15 data subject to change

CorePro GLASS LED candles and lusters

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	P45
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	2 kWh
EPREL Registration Number	387364
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
can it be used in closed luminaires	No


CorePro LEDLusterND2-25W P45 E27
827 CLG
CorePro LEDLusterND2-25W P45 E27
827 CLG
871951434776200
929001238792
929001238792
1
0.014 kg
8719514347762
10
8719514347779

Dimensional drawing




Product	D	С
CorePro LEDLusterND2-25W P45 E27 827 CLG	45 mm	78 mm

Photometric data








Light Distribution Diagram - CorePro LEDLusterND2-25W P45 E27 827 CLG


CorePro GLASS LED candles and lusters


Photometric data



General uniform lighting - CorePro LEDLusterND2-25W P45 E27 827 CLG

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDLusterND2-25W P45 E27 827 CLG



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.